





4 electromechanical relay 24Vac/dc SPDT 8A not pluggable

Series	CR
Code	XCR41
Type	CR4-1
HS code	85364190
INPUT TECHNICAL DATA	
Input rated voltage	24 Vac/dc $\pm 10\%$
Pull in / drop out voltage type	16.8 V / 2.4 V
Current consumption	16 mA $\pm 10\%$
Turn ON / OFF time	7 ms / 3 ms
Protection circuit	Free-wheel diode, Reverse polarity
Connection terminal	2.5 mm ² screw type pluggable
Input channels	4 not pluggable
OUTPUT TECHNICAL DATA	
Contact type	SPDT, 1 form C, AgNi
Nominal current	8 A (240 Vac)
Continuous current	8 A
Connection type	
GENERAL TECHNICAL DATA	
Operating temperature range	-20...+70°C
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 20
Overvoltage category / pollution degree	II / 2
Status indication	LED "DC OK" / LED "Relay"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	119x108x22.5 mm
Approximate weight	143 g
Mounting information	on a rail, side by side
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Spare part relay	8904042
APPROVALS AND MARKINGS	
	CE,



* Not-pluggable relay* AC/DC input voltage* Fast cabling with pluggable terminal blocks* Allow PNP and NPN command* Extremely compact dimensions
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

CR4-1 4 electromechanical relay 24Vac/dc
SPDT 8A not pluggable