

# PRODUCT DATASHEET Conversion kit + SubstiTUBE T5 AC HE21 10 W/3000 K 849.00 mm

SubstiTUBE T5 Conversion Kit single lamp | T5 LED tubes including conversion kit for single lamp luminaires



#### Areas of application

- Offices, public buildings
- Supermarkets and department stores
- Industry
- General illumination within ambient temperatures from -20...+45 °C

## **Product benefits**

- Only around 5 minutes per luminaire needed for rewiring
- No ECG compatibility issues
- No ECG maintenance necessary
- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- High luminous flux for sophisticated lighting tasks

### **Product features**

- Contains 10 SubstiTUBE T5 220-240V AC LED tubes and 10 conversion kits for single-lamp luminaires
- Conversion kit contains all necessary material for conversion of ECG luminaires to AC mains
- Detailed step-by-step instruction for guaranteed TÜV-certification available
- LED replacement for T5 fluorescent lamps with G5 base on AC mains
- Lamp tube made of glass with splinter protection e.g. for food industry applications



October 11, 2023, 16:12:39 Conversion kit + SubstiTUBE T5 AC HE21 10 W/3000 K 849.00 mm

- High color consistency:  $\leq$  5 SDCM
- Lifetime: up to 50,000 h
- Low flicker according to EU 2019/2020
- Type of protection: IP20

### **TECHNICAL DATA**

#### **Dimensions & Weight**

| Product weight                              | 1430.00 g   |
|---|---|
| Additional product data                     |   |
| Product remark                              | This product contains the following LED Tube as a light source:<br>SubstiTUBE T5 AC HE21 10 W/3000 K 849 mm, EAN: 4058075771741,<br>LED tube EEC: D, EPREL ID LED Tube: 1168776 |
|   |   |
| Certificates & Standards                    |   |
| Certificates & Standards Type of protection | IP20  |
|   | IP20  |

## Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

- Not suitable for operation with electronic control gear.

## DOWNLOAD DATA

|     | Documents and certificates |
|-----|----------------------------|
| PDF | Installation guide         |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4099854079436 | Shipping box<br>1            | 918 mm x 153 mm x 80 mm              | 2218.00 g    | 11.24 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **References / Links**

- For current information see www.ledvance.com/substitube

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.