



MASTER TL-D Super 80

MASTER TL-D Super 80 58W/865 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Flux measurement reference	Sphere				
Light Technical					
Color Code	865 [CCT of 6500K]				
Luminous Flux	5,000 lumen				
Color Designation	Cool Daylight				
Chromaticity Coordinate X (Nom)	0.313				
Chromaticity Coordinate Y (Nom)	0.337				
Correlated Color Temperature (Nom)	6500 K				
Luminous Efficacy (rated) (Nom)	81 lm/W				
Color rendering index (CRI)	80				
	-				
Operating and Electrical					
Power Consumption	59.4 W				

Lamp Current (Nom)	0.670 A				
Controls and Dimming					
Dimmable	Yes				
Mechanical and Housing					
Bulb Shape	T8 [26 mm (T8)]				
Approval and Application					
Mercury (Hg) Content (Nom)	1.7 mg				
Energy Consumption kWh/1000 h	60 kWh				
EPREL Registration Number	423,401				
Product Data					
Product Data Full product code	871150063225840				
	871150063225840 MASTER TL-D Super 80 58W/865 1SL/25				


Datasheet, 2023, May 16 data subject to change

MASTER TL-D Super 80

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927922086544
Full product name	MASTER TL-D Super 80 58W/865 1SL/25


EAN/UPC - Case	8711500632265
27 11 37 01 0 0 0 0 0 0	0711500052205

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,500.0 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm
58W/865 1SL/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 58W/865 1SL/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 58W/865 1SL/25

Life Expectancy Diagram - MASTER TL-D Super 80 58W/865 1SL/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 58W/865 1SL/25

