



# **TL-D Colored**

## TL-D Colored 36W Red 1SL/25

This TL-D lamp (tube diameter 26 mm) helps to create special effects and atmospheres or attract attention by using red, green, blue and yellow light. Apart from using the specific colors, it is also possible to mix the colors to create white light. This lamp offers a high light output, thanks to the use of basic powders. Application areas include shops and showrooms, bars and restaurants, demonstration areas, sign lighting and entertainment stores.

#### **Warnings and Safety**

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

| General Information      |                                 |  |  |  |  |
|--------------------------|---------------------------------|--|--|--|--|
| Cap-Base                 | G13 [Medium Bi-Pin Fluorescent] |  |  |  |  |
|                          |                                 |  |  |  |  |
| Light Technical          |                                 |  |  |  |  |
| Color Code               | 150<br>55 lumen                 |  |  |  |  |
| Luminous Flux            |                                 |  |  |  |  |
| Color Designation        | Red (HO)                        |  |  |  |  |
|                          |                                 |  |  |  |  |
| Operating and Electrical |                                 |  |  |  |  |
| Power Consumption        | 36.0 W                          |  |  |  |  |
| Lamp Current (Nom)       | 0.440 A                         |  |  |  |  |
| Voltage (Nom)            | 103 V                           |  |  |  |  |
| Voltage (Nom)            | 103 V                           |  |  |  |  |


| Controls and Dimming            |                             |  |  |  |  |
|---------------------------------|-----------------------------|--|--|--|--|
| Dimmable                        | Yes                         |  |  |  |  |
|                                 |                             |  |  |  |  |
| Mechanical and Housing          |                             |  |  |  |  |
| Bulb Shape                      | T8 [26 mm (T8)]             |  |  |  |  |
|                                 |                             |  |  |  |  |
| Approval and Application        |                             |  |  |  |  |
| Mercury (Hg) Content (Nom)      | 13.0 mg                     |  |  |  |  |
| Energy Consumption kWh/1000 h   | 51 kWh                      |  |  |  |  |
|                                 |                             |  |  |  |  |
| Product Data                    |                             |  |  |  |  |
| Full product code               | 871150072748040             |  |  |  |  |
| Order product name              | TL-D Colored 36W Red 1SL/25 |  |  |  |  |
| Order code                      | 928048501505                |  |  |  |  |
| Numerator - Quantity Per Pack   | tity Per Pack 1             |  |  |  |  |
| Numerator - Packs per outer box | 25                          |  |  |  |  |
|                                 |                             |  |  |  |  |

Datasheet, 2023, May 15 data subject to change

## **TL-D Colored**


| Material number (12NC) | 928048501505                |  |
|------------------------|-----------------------------|--|
| Full product name      | TL-D Colored 36W Red 1SL/25 |  |
| EAN/UPC - Case         | 8711500727497               |  |

### Dimensional drawing



| Product              | D (max) | A (max)    | B (max)    | B (min)    | C (max)    |
|----------------------|---------|------------|------------|------------|------------|
| TL-D Colored 36W Red | 28.0 mm | 1,199.4 mm | 1,206.5 mm | 1,204.1 mm | 1,213.6 mm |
| 1SL/25               |         |            |            |            |            |

#### Photometric data



Spectral Power Distribution Colour - TL-D Colored 36W Red 1SL/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.