

PRODUCT-DETAILS

RC5-1/133 RC5-1/133 Surge Suppressor



General Information	
Extended Product Type	RC5-1/133
Product ID	1SBN050100R1001
ABB Type Designation	RC 5-1/133, 50-133V AC / DC
EAN	3471522121257
Catalog Description	RC5-1/133 Surge Suppressor
Long Description	 RC5-1/133 is a RC type surge suppressor designed to reduce the maximum overvoltage peak value and to limit or even completely eliminate the high pre-damping voltage frequencies, when used with an AC operated conventional contactor for a rated control circuit voltage between 50133 V AC 50/60Hz. The operation of inductive circuits causes overvoltages, in particular on opening of the contactor coil. The electromagnetic energy stored in the coil during contactor closing is restored on opening in the form of surges, the slope and amplitude of which may rise to several kilovolts. A number of drawbacks are observed ranging from interference on the electronic devices to breakdown of insulators and even destruction of certain sensitive components. Advantages: the surge suppressor is clipped onto the top or side part in regards with the contactor or contactor relay base design without change in device overall dimensions. very fast clipping: attenuation of steep fronts and thus of high frequencies. No operating delays.

Ordering	
Minimum Order Quantity	2 piece
Customs Tariff Number	85363030
Product Main Type	Accessories for Block Contactors

Popular Downloads	
Data Sheet, Technical nformation	1SBC100214C020
nstructions and Manuals	1SBC101020M970
CAD Dimensional	2CDC001079B020
Drawing	
Dimensions	
Product Net Width	30.25 mn
Product Net Depth / Length	32.4 mr
Product Net Height	10.5 mr
Product Net Weight	0.012 kr
Technical	
Mounting Type	Clipped onto the top or bottom part of the contactor or contactor relay
Rated Control Circuit Voltage (U _c)	50 Hz / 60 Hz 50133 V AC
Rated Frequency (f)	Control Circuit 50 / 60 H
Suitable For	AS0 AS1
	AS1
	NS22I NS31I
	NS401
	NS44
	NS53I NS62I
	NS71
	NS80 VAS0
	VASU VASU
	VAS1
	A A1
	A1
	A2 A3
	A3 A4
	UA1
	UA2 UA3
	UA16R/
	UA26R/
	UA30R/ N22I
	N31
	N401 N441
	N53
	N62
	N711 N801
	N33/1
	N51/1 AX0
	AX0
	AX1
	AX1 AX2
	AX3
	AX4

Environmental		
Ambient Air Temperature	Operation -20 +70 °C	
RoHS Information	2CMT2021-006277	
WEEE B2C / B2B	Business To Business	

© 2023 ABB. All rights reserved.

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
Declaration of Conformity - CE	1SBD250816U1000
Declaration of Conformity - UKCA	1SBD250833U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
RINA Certificate	RINA_ELE172319XG001
UL Certificate	UL_20120523-E312527_1_3
UL Listing Card	UL E312527

Container Information	
Package Level 1 Units	blister 2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	96 mm
Package Level 1 Height	12 mm
Package Level 1 Gross Weight	0.024 kg
Package Level 1 EAN	3471522121257
Package Level 2 Units	box 324 piece
Package Level 2 Width	245 mm
Package Level 2 Depth / Length	75 mm
Package Level 2 Height	153 mm
Package Level 2 Gross Weight	3.888 kg
Package Level 3 Units	1200 piece

<u>Classifications</u>	
eClass	V11.0 : 27371392
E-Number (Sweden)	3228857
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
IDEA Granular Category Code (IGCC)	4906 >> Surge suppressers
UNSPSC	<u>39121610</u>

Categories

Low Voltage Products and Systems \rightarrow Control Products \rightarrow Contactors \rightarrow Block Contactors Accessories

