

# PRODUCT DATASHEET

## LS AY VAL -CP/P4/500/P

Connectors for RGB LED Strips | Connectors for RGB LED Strips



---

### Areas of application

- General indoor illumination

---

### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

## TECHNICAL DATA

### Electrical data

Nominal voltage	24 V
Nominal current	3000 mA

### Dimensions & Weight

Length	516 mm
Cable length	500 mm
Width	17.0 mm
Height	7 mm
Cable cross-section, input side	0.5 mm <sup>2</sup>
Product weight	5.00 g

### Colors & materials

Product color	Transparent/Black
---------------	-------------------

### Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Temperature range in operation	-15...+50 °C

### Certificates & Standards

Type of protection	IP65
--------------------	------

## LOGISTICAL DATA

Temperature range at storage	-20...+85 °C
------------------------------	--------------

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407893	BAG 2	80 mm x 120 mm x 5 mm	11.00 g	0.05 dm <sup>3</sup>
4058075407909	Shipping box 100	180 mm x 100 mm x 250 mm	629.00 g	4.50 dm <sup>3</sup>
4058075407916	Shipping box 1,000	520 mm x 380 mm x 280 mm	7057.00 g	55.33 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.