

SYSTEM SHIFT BASIC GLOBE RING

WLD+70013WW

See
more

On track luminaire SYSTEM SHIFT BASIC GLOBE RING, with a power of 10 W, high light efficacy 130 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.




Power	10 W	Voltage	48 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	60 °	Degree of protection (IP)	IP20

Technical data


Code	WLD+70013WW
Power	10 W
Nominal current	200 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1300 lm (360°)
Luminous flux**	300 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	60 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	90x150 mm
For use	Inside
Assembly method	NA SZYBĘ
Application	Inside
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file