



MASTER TL-D Super 80

MASTER TL-D Super 80 15W/840 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Flux measurement reference	Sphere				
Light Technical					
Color Code	840 [CCT of 4000K]				
Luminous Flux	1,000 lumen				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	0.38				
Chromaticity Coordinate Y (Nom)	0.38				
Correlated Color Temperature (Nom)	4000 K				
Luminous Efficacy (rated) (Nom)	67 lm/W				
Color rendering index (CRI)	82				
Operating and Electrical					
Power Consumption	15.5 W				

Lamp Current (Nom)	0.335 A				
Controls and Dimming					
Dimmable	Yes				
Mechanical and Housing					
Bulb Shape	T8 [26 mm (T8)]				
Approval and Application					
Mercury (Hg) Content (Nom)	1.7 mg				
Energy Consumption kWh/1000 h	16 kWh				
EPREL Registration Number	423,408				
Product Data					
Full product code	871150070280740				
Order product name	MASTER TL-D Super 80 15W/840 SLV/25				
Order code	927922284014				


Datasheet, 2023, May 16 data subject to change

MASTER TL-D Super 80

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927922284014
Full product name	MASTER TL-D Super 80 15W/840 SLV/25


EAN/UPC - Case	8711500722317

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80 15W/840	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm
SLV/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 15W/840 SLV/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 15W/840 SLV/25

Life Expectancy Diagram - MASTER TL-D Super 80 15W/840 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 15W/840 SLV/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.