



# **CoreLine Trunking Gen2**

## LL234X 7x1.5 BC

### LL234X | Coreline Trunking Gen2

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

### **Product data**

General Information	
Accessory color	White
Product family code	LL234X [Coreline Trunking Gen2]
Value ladder	Value
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Mechanical and Housing	
Overall length	3,400 mm
Overall width	80 mm
Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 80 x 3400 mm


Material	Steel
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IKO2 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Full product code	871951410852300
Order product name	LL234X 7x1.5 BC
Order code	910925867595
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	910925867595
Full product name	LL234X 7x1.5 BC
EAN/UPC - Case	8719514108523

Datasheet, 2023, May 22 data subject to change

# **CoreLine Trunking Gen2**



### Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.