

PRODUCT-DETAILS

OTM250E2CM230V

OTM250E2CM230V MOTORIZED C/O SWITCH



Algemene informatie

Type	OTM250E2CM230V
Artikelnummer	1SCA121211R1001
EAN	6417019524795
Omschrijving	OTM250E2CM230V MOTORIZED C/O SWITCH
Omschrijving	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Circular Value

Rapport over conflictmineralen (CMRT)	9AKK108467A5658
REACH-verklaring	1SCC011021D0201
RoHS-informatie	1SCC011020D0201

Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85365080
Land van herkomst	Finland (FI)

Popular Downloads

Gegevensblad, technische informatie	1SCC303003C0201
Instructies en handleidingen	1SCC303002M0204

Dimensions

Product netto breedte	238 mm
Product netto hoogte	150 mm
Product netto diepte	197 mm
Product netto gewicht	3.7 kg

Technical

Nominale bedrijfsstroom AC-21A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Nominale bedrijfsstroom AC-22A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Nominale bedrijfsstroom AC-31B (I_e)	(380 ... 415 V) 250 A
Nominale bedrijfsstroom AC-33B (I_e)	(380 ... 415 V) 250 A
Conventionele vrije-lucht thermische stroom (I_{th})	$\Theta = 40$ °C 250 A
Conventionele thermische stroom (I_{the})	Fully Enclosed 250 A
Nominale impuls grensvoltage (U_{imp})	12 kV
Nominaal isolatievoltage (U_i)	1000 V
Nominaal bedrijfsvoltage	1000 V
Nominale kortstondige grensstroom (I_{cw})	for 1 s 8 kiloampere rms
Motor operationeel voltage	220 ... 240 V AC
Vermogensverlies	6.5 W
Verontreinigingsgraad	3
Kleur verwerken	Black
Type verwerken	Direct mounted handle
Schakelbedieningsmechanisme	Mechanism at the End of the Switch
Afstand tussen fasen	Standard
Positie van lijnklemmen	Top In - Bottom Out, Bottom In - Top Out
Bedieningsmodus	Front operated
Montagetype	Base mounting

Aantal polen	2
Beschermingsgraad	Front IP20
Overgangstype	Open

Environmental

RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations

Conformiteitsverklaring - CE	No declaration needed
REACH-verklaring	1SCC011021D0201

Container Information

Pakketniveau 1 Units	1 stuk
Pakketniveau 1 Breedte	215 mm
Pakketniveau 1 Lengte	395 mm
Pakketniveau 1 Hoogte	215 mm
Pakketniveau 1 Brutogewicht	4.89 kg
Pakketniveau 1 EAN	6417019524795

Classifications

Object classificatiecode	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Lastscheider
ETIM 9	EC000216 - Lastscheider
eClass	V11.1 : 27371403
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601273

Categorieën

Laagspanningsproducten en -systemen → Schakelaars → Omschakelaars → Motorbediende omschakelaars

