

# NOCTIS LUX 2

SLI029043NW



See  
more

Floodlight NOCTIS LUX 2, with a power of 30 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.


IP65



Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2750 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>100 °</b>
Degree of protection (IP)	<b>IP65</b>		


## Technical data

Code	SLI029043NW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2750 lm (120°)
Luminous flux**	2650/2750 lm (360°)
Lamp efficacy	88 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	120x160x28 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC




## Related documents



 Declaration of Conformity



 Photometric file

