



Ref. Certif. No.

FR_708384

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Portable socket-outlet
Rewirable portable socket-outlets

Name and address of the applicant

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - FRANCE

Name and address of the manufacturer

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - FRANCE

Name and address of the factory

NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD
East Industrial Zone, Guanhaiwei Cixi City
315314 ZHEJIANG PROVINCE - CHINA

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

See Annex

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60884-1:2002 +A1:2006 +A2:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

ABND-ESH-P19121107

This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



LABORATOIRE CENTRAL DES
INDUSTRIES ELECTRIQUES
S.A.S au capital de 15.745.984 €
RCS Nanterre B 408 363 174
33 avenue du Général Leclerc
F - 92266 FONTENAY AUX ROSES

Signature:
Julier Gauthier
Certification Officer

Date: 12/05/2020

ANNEX

Technical characteristics

Model	Type Reference	Number of socket-outlets	Color of enclosure
RNS11X	6 945 73	3	white/grey
	6 945 74	3	black
	6 945 75	4	white/grey
	6 945 76	4	black
	6 945 77	5	white/grey
	6 945 78	5	black
	6 945 79	6	white/grey
	6 945 80	6	black

RATING AND MAIN CHARACTERISTICS

CLASSIFICATION

standard Sheet:	Standard Sheet III of CEE 7
rated current (A)	16A
rated load (W)	3680W
rated voltage (V)	250V
household voltage (V)	230V
degree of protection	IP20
provision for earthing	with earthing contact
method of connecting the cable	rewirable
type of terminals	screw-type
type of connections	-
colour	white/grey, black
socket-outlets	
multiple socket-outlets	
number of socket-outlets	16A : 3 to 6
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	portable type
method of installation	-



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Signature: *Julien Gauthier*
Certification Officer

Date: 12/05/2020