## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290024929

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	GU5.3		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

**Product parameters** 

	i i oddet para					
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	F			
Useful luminous flux ( $\phi$ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	460 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W	5,8	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90			
Outer Height	46	Spectral power	See image			
dimensions Width	51	distribution in the	in last page			

without separate control gear, lighting control parts and non-lighting control parts,	Depth	51	range 250 nm to 800 nm, at full-load	
if any (millimetre)	(2)	No. 1		25
Claim of equivale	nt power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	35
			Chromaticity coordinates (x and y)	0,434 0,403
Parameters for di	rectional light s	ources:		
Peak luminous int	ensity (cd)	600	Beam angle in degrees, or the range of beam angles that can be set	60
Parameters for LE	D and OLED lig	ht sources:	1	
R9 colour renderi	ng index value	0	Survival factor	0,90
the lumen mainte	enance factor	0,96		
(a), , not applicable.				

(a)'-' : not applicable;

(b)'-' : not applicable;

