

HVI LI 20 L6M SR2640 FSP1000 GFK AL V2A (819 258)



Figure without obligation



Type	HVI LI 20 L6M SR2640 FSP1000 GFK AL V2A
Part No.	819 258
Material of supporting tube	GRP / Al
Length of supporting tube	2640 mm
Transport length	2640 mm
Material of air-termination tip	StSt
Length of air-termination tip	1000 mm
Diameter Ø conductor	20 mm
Colour of conductor	grey •
Material of conductor	Cu
RAL colour	similar to 7000
Cross section of core	19 mm ²
Lightning current carrying capability (class / I _{imp})	H1 / 150 kA
Equivalent separation distance s (air)	≤ 45 cm
Material of insulation	PE
Material of sheath	PVC
Characteristics of sheath	UV stabilized and weather resistant
Connection diameter	10 mm
EB connection cable	strip StSt 2200 x 18 x 0.4 mm
Material of connection elements	StSt
Minimum order length	6 m
Max. gust wind speed	198 km/h
Max. free length	3040 mm
Min. clamping length	600 mm
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	6,97 kg
Customs tariff number	85389099
GTIN	4013364255418
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.