PHILIPS Lighting



A ↑ G

MASTER LED Strip

MAS LEDstrip 16.6W930 1830LM/M 5M

A complete family delivering superior light with great uniformity and safety. Choose the best fit for every projects, from 5 lumen packs/wattages, and 4 CCTs, and enjoy great reliable performance free of maintenance

Product data

General Information	
Driver included	No
Lighting Technology	LED
Warranty period	5 years
Light Technical	
Luminous Flux	1,830 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	110.00 lm/W
Color rendering index (CRI)	90
Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Input Voltage	24 V
Initial CLO power consumption	67 W
Average CLO power consumption	0 W
Power Consumption	67 W
Power Factor (Fraction)	1
Cable	Cable 0.3 m without plug
Number of products on MCB of 16 A type B	-
Protection class IEC	Safety class III
Controls and Dimming	
Dimmable	Yes

Control interface	depends on driver (1-10V, DALI)
Constant light output	Yes
Maximum dim level	10% (depends on dimmer, ELV)
Mechanical and Housing	
Reflector material	-
Overall length	5,000 mm
Overall width	8 mm
Overall height	1.3 mm
Dimensions (Height x Width x Depth)	1 x 8 x 5000 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK00 [No protection]
Net Weight (Piece)	0.100 kg
Approval and Application	
Energy Efficiency Class	F
EPREL Registration Number	620731
Glow-wire test	Temperature 650 °C, duration 30 s
CE mark	Yes
EU RoHS compliant	Yes
Ambient temperature range	-20 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

MASTER LED Strip

Initial chromaticity	(0.4338, 0.403) 3SDCM
Power consumption tolerance	+/-10%
Over Time Performance (IEC Co	mpliant)
Median useful life L70B50	60,000 hour(s)
Product Data	
Order product name	MAS LEDstrip 16.6W930 1830LM/M 5M
Full product name	MAS LEDstrip 16.6W930 1830LM/M 5M


Full product code	871951434458700
Order code	929002697602
Material Nr. (12NC)	929002697602
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514344587
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514344594

Dimensional drawing

Photometric data

		Strip 1 x 9290636976 3690K 1 x 1020in
hirinney Agen	Quantity animation diagram	UGI.degran
DOM	Advantation of the later	
1884		
KX XI		
$\sim \sim$	Minin	╡╇╋╬┥┙
10	Officiation fector of the	Lamenavia Titila
Auto Autor 18		
Dana abana		

General uniform lighting - MAS LEDstrip 16.6W930 1830LM/M 5M



Light Distribution Diagram - MAS LEDstrip 16.6W930 1830LM/M 5M



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2025, March 13 - data subject to change