


Kite Emergency Bulkhead



- Modern ultra-slim profile IP65 LED polycarbonate bulkhead
- Self-test as standard
- Aesthetically designed for modern appearance
- Supplied with self-adhesive legend
- 20mm side and rear cable entries
- Hinged screwless gear tray for ease of installation
- Viewing distance 20 metres



***	Escape route 2 metres wide (1 Lux minimum) *			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
Mounting Height (M)				
2.5	1.5	5	1.3	5.5
4	1.3	5	1.2	5.5
-	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
Mounting Height (M)				
2.5	2.1	6	2.1	6
4	2.4	7	2.4	7
6	2.1	7	2.1	7

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 40°C	L70 50,000	120°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE	TRADE
AKTLED/3M/ST	Daylight - Maintained / Non-Maintained	3.4W	6500K	138lm	66.7lm	£52.50

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/22/LI	3.2V 1000mAh Li-FePO4 Replacement Battery	£5.15