

**UNITRONIC® LAN 200 U/UTP Cat. 5e LSZH
4x2xAWG 24/1**
DB2170173
 valid from: 20.09.2013

Application

Data cable for transmission of digital and analog signals up to 200 MHz. The cable is designed for horizontal cabling systems as connection between a floor distribution and the telecommunication outlets (TO's). According to TIA/EIA-568-A, ISO/IEC 11801 2nd edition, EN 50173, EN 50288-3-1, IEC 61156-5. For application in LANs like IEEE 802.3: 10Base-T, 100Base-T, 1000Base-T; FDDI; ISDN; ATM.

Design

Conductor	bare copper AWG 24/1, massive
Insulation	PE, ca. 0.96 mm core Ø
Core identification code	acc. to IEC 708-1
Stranding	4 pairs, stranded to bundle
Outer sheath	halogen free compound (FRNC), grey similar to RAL 7035, outer Ø: ca. 5.4 mm

Electrical properties at 20° C

Resistance (loop)	max. 190 Ω/km, acc. to VDE 0812
Insulation resistance	min. 5 GΩxkm
Mutual capacitance	nom. 50 nF/km
Characteristic impedance	100 Ω ±5 Ω (at 100 MHz)
Velocity of propagation	ca. 0.67 c
Signal propagation time	<510 ns/100m
Delay difference	<20 ns/100m
Test voltage	700 V (AC)

Transmission properties

f [MHz]	Attenuation nom. [dB/100m]	NEXT nom. [dB]	ACR nom. [dB/100m]	ELFEXT nom. [dB/100m]	RL nom. [dB]
1	1.8	80	78.2	65	23
4	3.7	75	71.3	56	27
10	5.9	70	64.1	45	30
16	7.4	68	60.6	41	30
20	8.3	65	56.7	39	30
31.25	10.3	60	49.7	35	30
62.5	14.4	56	41.6	30	30
100	19.2	52	32.8	25	28
155	22.1	47	24.9	23	26
200	24.8	44	20.2	21	24

**UNITRONIC® LAN 200 U/UTP Cat. 5e LSZH
4x2xAWG 24/1**DB2170173
valid from: 20.09.2013**Mechanical and thermal properties**

Minimum bending radius	during installation: 8 x cable Ø static: 4 x cable Ø
Permissible temperature range	during installation: 0° C up to +50° C static: -20° C up to +60° C
Flame propagation	flame retardant acc. to IEC 60332-1-2
Smoke gas test	acc. to EN 50267-2-1/ EN 50267-2-2, IEC 60754-1/ IEC 60754-2, IEC 61034/EN 61034
General requirements	Dangerous and forbidden substances acc. to RoHS directive (2002/95/EG) are not allowed to the manufacturing.