



Push-in  
terminal block 4mm<sup>2</sup> fuse-holder, 1-level, grey color with cartridge



Code	EFS402GR
Type	CPFE.4 + EFS.4/GR
HS code	85369010
Colour	Grey
<b>TECHNICAL FEATURES</b>	
Function/Type	Fuse-holder 5x20
Rated cross-section	4 mm <sup>2</sup>
<b>Connecting capacity</b>	
Flexible wire	0.2-6 mm <sup>2</sup>
Rigid wire	0.2-6 mm <sup>2</sup>
Wire with ferrule - ferrule type	4 mm <sup>2</sup> - WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	250 V
Maximum current (rated cross-section)	6.3 A (1)
Caliber	A4
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	6.3 A (1)
Section (min-max)	24-10 (AWG)
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
Rated impulse withstand voltage / pollution degree	4 kV / 3
Insulation stripping length	10 mm
Width (pitch)	6.2 mm
Length	55.2 mm
Height mounted on TH35-7.5/TH35-15/G32	67.1 / 74.6 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
Grey	EFC.4/PT/GR (cod. EFC401GR)
Blue	EFC.4/PT/BL (cod. EFC401BL)
Thickness	1.5 mm
Cross-connection	EFB.4/.../... (cod. EFB04...)
Rated current carrying capacity IEC/ATEX	32 A
Coloured partition plate	DFE.1+1/R (cod. DFE01R)
<b>Marking</b>	
Single marking tag	CNU/8/51 (cod. NU0851S), CNU/10/51 (cod. NU1051S)
Single marking tag for pitch insertion	CNU/8/61 (cod. NU0861S), CNU/10/61 (cod. NU1061S)
Fuse type	5x20 mm (1)
Conductive element	CO/5 (cod. VL103)
Light alarm circuit (12...48 V)	CIL/12-24-48 (cod. CB518)
Light alarm circuit (110...230 V)	CIL/115-230 (cod. CB523)
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
<b>APPROVALS AND MARKINGS</b>	
	...



\* Suitable for 5x20 mm fuses\* Accessory with alarm LED, available separately\* Accessory with 1 A or 3 A diode, available separately  
1 For more details on accessories, refer to the relevant chapters 2 (1) Value limited by the certification rating of the fuse

## DESCRIZIONE DEL PRODOTTO

CPFE.4+EFS.4/GR Push-in terminal block 4mm<sup>2</sup> fuse-holder,  
1-level, grey color with cartridge