


# ANDHO mini

722185.002.76 | Spotlights



Spotlights  
4051859761549  
L 190, B 114, H 152

Ceiling mounting, pedestal mount  
traffic white, matt (RAL 9016)



Surface-mounted LED projector in a timeless design. Housing: die-cast aluminium, seawater resistant powder-coated. Integral membrane valve for pressure compensation and avoidance of condensation. MIRO-SILVER® reflectors for outstanding efficiency or polycarbonate lenses for the best uniformity of the light cone. Cover clear single-pane toughened glass, edge printed. COB LED with socket for easy replacement. Projector: horizontal rotation range: 360°, vertical swivel range: 90°. Lockable projector orientation. Driver integrated.


## Product specifications

Length L	190 mm
Width B	114 mm
Height H	152 mm
Weight	2.1 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	3100 lm
System power	27 W
System efficiency	115 lm/W
Glare evaluation UGR (4H 8H)	19
Beam angle	40°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	2
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	31
Luminaires on B16A fuse	50
Luminaires on C10A fuse	52
Luminaires on C16A fuse	85
Inrush current / Inrush current duration	5 A / 50 µs
CIE Flux Code / CEN Flux Code	96 100 100 100 100
Type of protection	IP 65
Protection class	II
Filament test	960 °C
Impact resistance	IK07
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE

## Accessories




982165.003  
Snap-on hood



982168.003  
Barn door shutter



982162.003  
Louvres



982159.000  
Reeded glass