

# PRODUCT DATASHEET SMART+ WIFI REMOTE CONTROLLER USB Black

SMART+ WIFI REMOTE CONTROL USB-C | SMART+ remote controls with WiFi technology



# Areas of application

- Smart Home in indoor and outdoor
- Wherever smart control and automation are to be implemented in compatible smart home systems

# Product benefits

- Control of SMART+ Wifi products without using voice control and APP
- Selection of preset light scenes via remote control
- High-quality aluminum housing for premium feel and appearance

## Product features

- On/off and dimming
- Adjustable light color via Tunable White: Warm White to Cool White
- Light scenes adjustable
- Network protocol: WiFi (2.4 GHz)
- Smart control for adjustable color temperature and RGB color control

### **TECHNICAL DATA**

## Electrical data

Nominal voltage	3,7 V
Operating mode	Battery

# Dimensions & Weight



Product weight	52.00 g
Length	120.00 mm
Width	39.00 mm
Height	12.40 mm

# Colors & materials

Product color	Black
Body material	Aluminum/Plastic

# Temperatures & operating conditions

Ambient temperature range	-10+35 °C
---------------------------	-----------

# Capabilities

Dimmable	No
----------	----

## Certificates & Standards

Standards	CE / UKCA
Protection class	III
Type of protection	IP20

# **EQUIPMENT / ACCESSORIES**

- Rechargeable battery integrated and easy charging via USB-C
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Charging cable included

## Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in
  the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or
  cutting of a battery, that can result in an explosion.

## **DOWNLOAD DATA**

	Documents and certificates Document name	
PDF	User instruction / safety instructions	SMART+ WIFI REMOTE CONTROLLER USB
PDF	Declarations of conformity	SMART WIFI REMOTE CONTROLLER
PDF	Declarations of conformity UKCA	SMART WIFI REMOTE CONTROLLER

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854294280	Folding box 1	61 mm x 78 mm x 143 mm	111.00 g	0.68 dm <sup>3</sup>
4099854294297	Shipping box 4	166 mm x 153 mm x 138 mm	530.00 g	3.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.