


Monarch Lithium Bulkhead



- Ultra-slim profile LED polycarbonate self-test bulkhead
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Supplied with self-adhesive legend
- 20mm side, end and rear cable entries
- Hinged screwless gear tray for ease of installation
- Viewing distance 18 metres



***	Escape route 2 metres wide (1 Lux minimum) *			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	1.6	5	1.5	5
4	0.5	2.3	0.4	2.3
6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	2.2	5.5	2.2	5.5
4	2.4	6	2.4	6
6	1.5	6	1.5	6

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
220-240V	50Hz	5°C to 40°C	L70 54,000	150°	2	IP65	IK10

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE	TRADE
AMOLED/LI/3M/ST	Daylight - Maintained / Non-Maintained	3W	6000K	123lm	62lm	£48.50

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/18	3.2V 1500mAh Li-FePO4 Lithium Replacement Battery	£13.60

