



PRODUCT DATASHEET

FLASHLIGHT HEADLAMP BATTERY COMPACT

FLASHLIGHT HEADLAMP BATTERY COMPACT | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 4 operating modes: 1 press: bright light 100 lm, 2nd press: soft light 30 lm, 3rd press: red light is turn on, 4th press: red light flashing
- 3 hours of running at full brightness
- Powered by 3 AAA batteries (not included)
- Type of protection: IP22

Product features

- Hinge to adjust light direction
- Can be attached to helmet, cap etc.
- Adjustable head strap included.
- Durable and high-quality materials
- Convenient button for switching modes

TECHNICAL DATA

Electrical data

Nominal wattage	2.20 W
Inrush current	550 mA
Inrush current time T_{h50}	0.5 s
Operating mode	Battery

Photometrical data

Luminous flux	100 lm
Luminous efficacy	45 lm/W
Color temperature	6500 K
Light color (designation)	Cool White
Color rendering index Ra	80

Dimensions & Weight

Length	60.00 mm
Width	44.00 mm
Height	43.00 mm
Product weight	48.00 g

Materials & Colors

Product color	Orange
Housing color	Orange
Body material	Acrylonitrile butadiene styrene (ABS)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Dimmable	No
Adjustable	No
With light source	Yes

Lifespan



Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Documents and certificates	Document name
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	CE Declaration Flashlight

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175749	Blister 1	140 mm x 110 mm x 31 mm	57.00 g	0.48 dm ³
4099854175756	Shipping box 60	345 mm x 280 mm x 340 mm	4018.00 g	32.84 dm ³
4099854583957	Shipping box 10	290 mm x 190 mm x 175 mm	884.00 g	9.64 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.