Product Data Sheet

GWA1221


Connected SMART HOME




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Power supply	100 ÷ 240 V ac - 50/60 Hz	Power	4-150 W 240 V ac
No. modules	1	No. output channels	1
Radio connections	Zigbee (IEEE 802.15.4)	Standard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN
		606	69-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000
Working temperature	-5 ÷ +45 °C	Relative humidity (non-conder	
Power output Zigbee	10 dBm	Dispersible max power (W)	5,7
Wiring terminals	With screw	Terminal tightening capacity stranded cables (mm²)	Max. 1,5
Terminal tightening ca solid cables (mm²)	pacity Max. 1,5	Category	Dimmers
No. input channels	2 (for local command replication or sending additional Zigbee commands)	Input voltage	Mains supply voltage
IP degree	IP20 (with button key)	240 V ac Incandescent-haloge	en lamps 4-150 W
240 V ac LED lamps	4-150W (max 10 lamps)	Loads piloted from electronic	transformers 240 V ac 4-150 VA
LED colour	Blue	Local control	Via 2 front push buttons (to complete with button key)
Zigbee control extensi	on if Massa(12e Ziigdo ae Econom Salvala Battip batteed (Solithi Filio fut rpodissim jouttons)	Load control	Trailing edge

DIMENSIONAL





TECHNICAL SYMBOLOGY



IP20 (with button key)

STANDARDS/APPROVALS

