



# CorePro Glass LED bulbs



# CorePro LEDBulb8.5-75W E27 A60 840 FR G

Featuring a classic heritage design, these filament LED lamps combine the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. A very easy choice for people who are looking for a retrofit LED replacement, these CorePro LED bulbs provide 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light in a vintage style. CorePro LED lighting that offers a lifetime of 15,000 hours to reduce maintenance costs.

### **Product data**

General Information	
Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	1,055 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	8.5 W
Lamp Current (Nom)	70 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.52
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	50 °C


Datasheet, 2025, March 17 data subject to change

# CorePro Glass LED bulbs

Controls and Dimming	
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A60
Net Weight (Piece)	0.030 kg
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	9 kWh
EPREL Registration Number	387426
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4


Application Conditions		
can it be used in closed luminaires	No	
Product Data		
Order product name	CorePro LEDBulb8.5-75W E27 A60	
	840 FR G	
Full product name	CorePro LEDBulb8.5-75W E27 A60	
	840 FR G	
Full product code	871951437753000	
Order code	929002025892	
Material Nr. (12NC)	929002025892	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8719514377530	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8719514377547	

# Dimensional drawing




Product	D	С
CorePro LEDBulb8.5-75W E27 A60 840 FR G	60 mm	104 mm

## Photometric data




General uniform lighting - CorePro LEDBulb8.5-75W E27 A60 840 FR G



Spectral Power Distribution Colour - CorePro LEDBulb8.5-75W E27 A60 840 FR G


## CorePro Glass LED bulbs


### Photometric data



Light Distribution Diagram - CorePro LEDBulb8.5-75W E27 A60 840 FR G

### Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDBulb8.5-75W E27 A60 840 FR G



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.