

ALGINE

SLI035014WW

LED panel ALGINE, with a power of 32 W, high light efficacy 103 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for surface, recessed and suspended mounting.

IK06



Power	32 W	Voltage	230 V
Luminous flux*	3300 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20

Technical data

Code	SLI035014WW
Power	32 W
Nominal current	154 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	32 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	3300 lm (120°)
Luminous flux**	3200 lm (360°)
Lamp efficacy	103 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	295x1195x10 mm
Mounting hole	275x1175 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC



Related documents

[User manual](#)[Declaration of Conformity](#)[Photometric file](#)

