Product Data Sheet

GWA1202


Connected SMART HOME




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Output contacts		1 NA / NC 2 A (AC1) 240 V ac	Power supply	100 ÷ 240 V ac - 50/60 Hz
No. of channels		0	No. modules	2
No. output channels		1	Radio connections	Zigbee (IEEE 802.15.4)
Standard	2014/53/EU, 2011/65/EU	+ 2015/863, EN 60669-2-1, EN	Working temperature	-5 ÷ +45 °C
	60669-1, EN 301 489-1, EN 30	1 489-17, EN 300 328, EN IEC		
		63000		
Relative humidity (non-condensative)		Max 93%	Power output Zigbee	10 dBm
Dispersible max power (W)		2,6	Wiring terminals	With screw
Terminal tightening capacity		Max. 1,5	Terminal tightening ca	pacity Max. 1,5
stranded cables (mm²)			solid cables (mm²)	
Category		Axial 2-way switch connected	No. input channels	2 (for local command replication or sending additional Zigbee
				commands)
Input voltage		Mains supply voltage	IP degree	IP20 (with button key)
240 V ac Incandescent-halogen lamps 4-500 W		240 V ac LED lamps	4-100 W	
Loads piloted from electronic transformers 240 V ac 4-250 VA		LED colour	Blue	
Local control	Via front push butto	on (to complete with button key)	Power supply of EGO	SMART plate Yes
Zigbee control extension if installed in an EGO SMART plateY(&:-(1FZift)redictor)mmand)			Functions	Timed load control, indicative measurement of active power and
				consumed energy

DIMENSIONAL





TECHNICAL SYMBOLOGY



IP20 (with button

STANDARDS/APPROVALS

