

WLD+40004_SMART

WLD+40004_SMART



Power	6 W	Voltage	48 V
Colour temperature	3000/4000/6000 K	Colour of light	CCT
Beam angle	24 °	Degree of protection (IP)	IP20


Technical data

Code	WLD+40004_SMART
Power	6 W
Nominal current	115 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	500 lm (360°)
Luminous flux**	350 lm (360°)
Lamp efficacy	83 lm/W
Luminous intensity	1050 cd
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	24 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	35x140x178 mm
For use	Inside
Assembly method	NA SZYŃĘ
Application	Inside
Made in	PRC
Other	CCT/DIM ,



Related documents



 User manual



 Declaration of Conformity

	<p>Luminaire assembly within the track on "click" and its free arrangement</p>	
<p>Montaż oprawy w obrobie szyby na „click” oraz możliwość swobodnego jej przesuwania</p>		