

NOCTIS LUX 3

SLI029055WW_CZUJNIK_PW



See
more

Floodlight NOCTIS LUX 3, with a power of 50 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP44


IK07



Power	50 W	Voltage	230 V
Luminous flux*	4300 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	100 °
IK	07	Degree of protection (IP)	IP44


Technical data

Code	SLI029055WW_CZUJNIK_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (120°)
Luminous flux**	4300 lm (360°)
Lamp efficacy	86 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	180x215x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



Related documents



 Declaration of Conformity



 Photometric file

