

PRODUCT-DETAILS

MC1C400ATWN

MC1C400ATWN Mini Contactor 220 V DC - 4 NO - 0 NC - Screw Terminals



Informations générales

Extension du type de produit	MC1C400ATWN
Code de produit	1SAL220340R9901
EAN	4013614543005
Description courte	MC1C400ATWN Mini Contactor 220 V DC - 4 NO - 0 NC - Screw Terminals
Description longue	The MC1C400ATWN mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is equipped with an extended operating limits coil and it's suitable for wall or rail mounting.

Commande

Quantité minimum	1 pièce
Code douanier	85365080

Popular Downloads

Instructions et manuels	2CDC103061M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	45 mm
Produit Hauteur Net	48 mm
Produit Longueur Net	68 mm
Poids net	0.25 kg

Technique

Nombre de pôles	4
Mini Contactor Type	Mini Contactor
Tension	Circuit principal 690 V AC Circuit principal 440 V DC
Fréquence assignée (f)	Circuit de commande DC Circuit principal 50 Hz Circuit principal 60 Hz Circuit principal DC
Tension assignée de tenue aux chocs (U_{imp})	Circuit principal 6 kV
Tension assignée d'isolement (U_i)	750 V
Number of Main Contacts NC	0
Number of Main Contacts NO	4
Courant assignée d'emploi AC-1 (I_e)	(690 V) 55 °C 20 A (690 V) 70 °C 16 A (230 V) 55 °C 20 A (230 V) 70 °C 16 A (400 V) 55 °C 20 A (400 V) 70 °C 16 A (500 V) 55 °C 20 A (500 V) 70 °C 16 A
Puissance assignée d'emploi AC-3 (P_e)	(230 V) Three Phase 2.2 kW (400 V) Three Phase 4 kW (500 V) Three Phase 4 kW (690 V) Three Phase, NO 4 kW
Courant assigné de courte durée admissible (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 72 A
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Courant thermique conventionnel à l'air libre (I_{th})	Main Circuit 20 A
Rated Control Circuit Voltage (U_c)	220 V DC
Plage d'utilisation de la bobine selon	(acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x U_c (at $\theta \leq 55$ °C)
Indice de protection	Control Circuit Terminals IP20 Main Circuit Terminals IP20
Durabilite mecanique	10000000 cycle
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-15) 360 cycles per hour (AC-3) 1200 cycles per hour (DC-1) 600 cycles per hour (DC-13) 360 cycles per hour (DC-3) 600 cycles per hour
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1x 0.75 ... 4 mm ²

	Rigid 2x 0.75 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Wire Stripping Length	Control Circuit 9 mm Main Circuit 9 mm
Couple de serrage	Control Circuit 0.8 N·m Main Circuit 0.8 ... 1.0 N·m
Recommended Screw Driver	Pozidriv 2
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Power Loss	at Rated Operating Conditions AC-1 per Pole 0.7 W
Normes et standards	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Circuit principal 600 V AC
Full Load Amps Motor Use	(115 V AC) Single Phase 9.8 A (200 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (230 V AC) Single Phase 10 A (440 ... 480 V AC) Three Phase 7.6 A (550 ... 600 V AC) Three Phase 6.1 A
Puissance nominale UL/CSA	(115 V AC) Single Phase 0.5 Hp (200 V AC) Three Phase 3 Hp (220 ... 240 V AC) Three Phase 3 Hp (230 V AC) Single Phase 1.5 Hp (440 ... 480 V AC) Three Phase 5 Hp (550 ... 600 V AC) Three Phase 5 Hp
General Use Rating UL/CSA	(600 V AC) 20 A
Connecting Capacity Main Circuit UL/CSA	Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Control Circuit 7 in·lb Main Circuit 7 in·lb

Environnement

Température de l'air ambiant	Operation -40 ... +70 °C Storage -55 ... +80 °C
Altitude de fonctionnement maximale autorisée	3000 m
Résistance aux chocs selon CEI 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificats et Déclarations (Numéro de document)

Certificat BV	1SAA971000-0201
CB Certificate	1SAA971000-2001
CQC Certificate	CQC2019010304197131

Declaration of Conformity - CCC	2020980304001602
Déclaration de Conformité - CE	1SAD101100-3201
Declaration of Conformity - UKCA	1SAD201100-3201
Certificat RINA	1SAA971000-0801
Certificat UL	E191658-19880826

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	46 mm
Emballage Niveau 1 Hauteur	70 mm
Emballage Niveau 1 Longueur	49 mm
Emballage Niveau 1 Poids	0.255 kg
Emballage Niveau 1 EAN	4013614543005
Emballage Niveau 2 Unités	box 10 pièce
Emballage Niveau 2 Largeur	243 mm
Emballage Niveau 2 Hauteur	80 mm
Emballage Niveau 2 Longueur	106 mm
Emballage Niveau 2 Poids	2.61 kg
Emballage Niveau 2 EAN	4013614543500

Classifications

Code de classification d'objet	Q
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - contacteur de puissance pour commutation de courant alternatif
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
E-Number (Finland)	3709701

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Mini contacteurs

