

# SLI035070CW\_35W\_CAS

SLI035070CW\_35W\_CAS



Power	<b>35 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3900 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

---

Code	SLI035070CW_35W_CAS
Power	35 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3900 lm (360°)
Luminous flux**	3900 lm (360°)
Lamp efficacy	111 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	CASAMBI
Working temperature range	-20/+40 °
Lifespan	25000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x10 mm
Mounting hole	600x600 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC