

ORBITO

SLI043019WW_PW

See
more

LED luminaire ORBITO, with power regulation on the power supply (6-20 W), high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.




Power	6-20 W	Voltage	230 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	40 °	UGR	<19
IK	06	Degree of protection (IP)	IP44

Technical data

Code	SLI043019WW_PW
Power	6-20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50-60 Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	2200 lm (360°)
Luminous flux**	500-1700 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	3000 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	06
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	139x85 mm
Mounting hole	115 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

