

PRODUCT DATASHEET

TruSys® PFM ENERGY RAIL 8P 3000

TruSys® PERFORMANCE ENERGY RAIL 8 POLE | 8-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, garages, hardware stores



PERFOR-
MANCE
CLASS

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 8 core cable
- Different lengths available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	3150 mm
Width	70.2 mm
Height	38.8 mm
Product weight	3260.00 g

Materials & Colors

Product color	White
---------------	-------

Application & Mounting

Ambient temperature range	-25...+60 °C
Type of protection	IP20
Mounting type	Surface
Mounting location	Ceiling
With light source	No



Certificates & Standards

Standards	CE
-----------	----

EQUIPMENT / ACCESSORIES

– Various accessories available

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	TRUNKING SYSTEM PFM EM
CAD/BIM files		Document name
	CAD STEP 3D	TRUSYS PFM ER 3000

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.