

# LIMEA VARIO

SLI047007\_PW

See  
more

Hermetic luminaire LIMEA VARIO with the possibility of changing the light color (CCT), with power regulation on the power supply (30/40/50 W), high light efficacy 175 lm/W. Thanks to the ability to change the color temperature (CCT) in the range from 3000K to 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



CCT

IP65

IK08



Power	<b>30/40/50 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8750 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>120 °</b>
IK	<b>08</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data


---

Code	SLI047007_PW
Power	30/40/50 W
Nominal current	215 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	8750 lm (360°)
Luminous flux**	4650/6200/7750 lm (360°)
Lamp efficacy	175 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PC/PC
IK	08
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	1500x86x70 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

## Related documents

---



 User manual

