Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 8711500193452 |
|-------------------|---------------|
|-------------------|---------------|

| _ | • | | | |
|------|----|-------|--------|-----|
| Tyna | Λt | lioht | source | ٠. |
| IVDE | vı | HEILL | JUUILE | - • |

| Lighting technology used: | HPS | Non-directional or directional: | NDLS |
|-------------------------------|------|---------------------------------|-----------|
| Light source cap-type | E40 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | Non-clear |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |
| Dundust novementors | | | |

Product parameters

| Product parameters | | | | | |
|-----------------------------------|--|----------------------------|--|--------------|--|
| Parameter | | Value | Parameter | Value | |
| | General product parameters: | | | | |
| O , | mption in on- 100 h), rounded est integer | 408 | Energy efficiency class | Е | |
| indicating if it r in a sphere (3 | us flux (фuse), refers to the flux 60º), in a wide in a narrow cone | 55 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 000 | |
| On-mode pressed in W | oower (P _{on}), | 408,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| for CLS, expre | ndby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 125 | |
| Outer | Height | 290 | Spectral power | See image | |
| dimensions | Width | 122 | distribution in the | in last page | |
| without | Depth | 122 | 1 | Page 1 / 3 | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|--------------------------------------|----------------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,535 0,420 |

(a)'-': not applicable; (b)'-': not applicable;

