



MASTER TL-D Super 80

MASTER TL-D Super 80 14W/840 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	860 lumen
Color Designation	Cool Daylight
Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	63 lm/W
Color rendering index (CRI)	83
Operating and Electrical	
Power Consumption	14.2 W

Lamp Current (Nom)	0.380 A
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T8 [26 mm (T8)]
Approval and Application	
Mercury (Hg) Content (Max)	2 mg
Mercury (Hg) Content (Nom)	2 mg
Energy Consumption kWh/1000 h	15 kWh
EPREL Registration Number	423,504
Product Data	·
Full product code	871150095381040
Order product name	MASTER TL-D Super 80 14W/840 SLV/25


Datasheet, 2023, May 16 data subject to change

MASTER TL-D Super 80

Order code	928024384001
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	928024384001

Full product name	MASTER TL-D Super 80 14W/840 SLV/25
EAN/UPC - Case	8711500953827

Dimensional drawing




 Product
 D (max)
 A (max)
 B (max)
 B (min)
 C (max)

 MASTER TL-D Super 80 14W/840
 28 mm
 361.2 mm
 368.3 mm
 365.9 mm
 375.4 mm


 SLV/25


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 14W/840 SLV/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 14W/840 SLV/25

Life Expectancy Diagram - MASTER TL-D Super 80 14W/840 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 14W/840 SLV/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.