


PRODUCT-DETAILS

MC1C301ARWDD-RAIL

MC1C301ARWDD-RAIL Mini Contactor 17 ... 30 V DC - 3 NO - 0 NC - Ring-Tongue Terminals



Algemene informatie

Type	MC1C301ARWDD-RAIL
Artikelnummer	1SAL102121R9911
EAN	4013614548765
Omschrijving	MC1C301ARWDD-RAIL Mini Contactor 17 ... 30 V DC - 3 NO - 0 NC - Ring-Tongue Terminals

Omschrijving	The MC1C301ARWDD-RAIL mini contactor is a dimension optimized 3 pole contactor with 1 NC auxiliary contact and special screw terminals for a connection with ring tongue ferrules. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buldings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is suitable for wall or rail mounting.
--------------	--

Ordering

Minimale bestelhoeveelheid	1 stuk
Numer douanetarief	85365080

Popular Downloads

Instructies en handleidingen	2CDC103061M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product netto breedte	45 mm
Product netto hoogte	48 mm
Product netto diepte	68 mm
Product netto gewicht	0.25 kg

Technical

Aantal polen	3
Type minicontactor	Mini Contactor
Nominaal bedrijfsvoltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 440 V DC Main Circuit 690 V AC Main Circuit 440 V DC
Toegekende frequentie (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Nominale impuls grensvoltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 6 kV
Nominaal isolatievoltage (U_i)	750 V
Aantal hoofdcontacten NC	0
Aantal hoofdcontacten NO	3
Nominale bedrijfsstroom AC-1 (I_e)	(690 V) 55 °C 20 A (690 V) 70 °C 16 A (230 V) 55 °C 20 A (230 V) 70 °C 16 A (400 V) 55 °C 20 A (400 V) 70 °C 16 A (500 V) 55 °C 20 A (500 V) 70 °C 16 A
Nominale bedrijfsvermogen AC-3 (P_e)	(230 V) Three Phase 2.2 kW (400 V) Three Phase 4 kW (500 V) Three Phase 4 kW (690 V) Three Phase, NO 4 kW
Nominale kortstondige grensstroom (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 72 A
Aantal hulpcontacten NC	1
Aantal hulpcontacten NO	0
Nominale bedrijfsstroom AC-15 (I_e)	(240 V) 6 A (400 V) 4 A (500 V) 2.5 A (690 V) 1.5 A
Nominale bedrijfsstroom DC-13 (I_e)	(24 V) 5 A (48 V) 2.5 A

	(125 V) 0.55 A (250 V) 0.3 A (440 V) 0.15 A
Conventionele vrije-lucht thermische stroom (I_{th})	Auxiliary Circuit 10 A Main Circuit 20 A
Nominale stuurstroomkringspanning (U_c)	17 ... 30 V DC
Spoel operationele limieten	(acc. to IEC 60947-4-1) for DC supply U_c Min. ... U_c Max. (at $\theta \leq 55^\circ\text{C}$)
Beschermingsgraad	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20
Mechanische duurzaamheid	10000000 cycle
Minimale schakelcapaciteit	Auxiliary Circuit 17 V Auxiliary Circuit 5 mA
Maximale elektrische schakelfrequentie	(AC-1) 300 omwentelingen per uur (AC-15) 360 omwentelingen per uur (AC-3) 1200 omwentelingen per uur (DC-1) 600 omwentelingen per uur (DC-13) 360 omwentelingen per uur (DC-3) 600 omwentelingen per uur
Verbindingscapaciteit hoofdcircuit	Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Verbindingscapaciteit hulpcircuit	Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Verbindingscapaciteit controlecircuit	Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Kabelstriplengte	Auxiliary Circuit 9 mm Control Circuit 9 mm Main Circuit 9 mm
Aanhaalmoment	Auxiliary Circuit 0.8 ... 1.0 N·m Control Circuit 0.8 N·m Main Circuit 0.8 ... 1.0 N·m
Aanbevolen schroevendraaier	Pozitief 2
Montage op DIN-rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Vermogensverlies	at Rated Operating Conditions AC-1 per Pole 0.7 W
Normen	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 UL 60947-5-1

Technical UL/CSA

Maximale bedrijfsspanning UL/CSA	Main Circuit 600 V AC
Vollast amps motorgebruik	(115 V AC) Single Phase 9.8 A (200 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (230 V AC) Single Phase 10 A (440 ... 480 V AC) Three Phase 7.6 A (550 ... 600 V AC) Three Phase 6.1 A
Paardenkrachtklasse	(115 V AC) Single Phase 0.5 Hp

UL/CSA	(200 V AC) Three Phase 3 Hp (220 ... 240 V AC) Three Phase 3 Hp (230 V AC) Single Phase 1.5 Hp (440 ... 480 V AC) Three Phase 5 Hp (550 ... 600 V AC) Three Phase 5 Hp
Algemeen gebruik klasse UL/CSA	(600 V AC) 20 A
Contactklasse UL/CSA	A600 Q600
Verbindingscapaciteit hoofdcircuit UL/CSA	Stranded 1/2x 18-12 AWG
Verbindingscapaciteit hulpcircuit UL/CSA	Stranded 1/2x 18-12 AWG
Aanhaalmoment UL/CSA	Auxiliary Circuit 7 in-lb Control Circuit 7 in-lb Main Circuit 7 in-lb

Environmental

Omgevingsluchttemperatuur	Werking -40 ... +70 °C Opslag -55 ... +80 °C
Maximale werkhoogte toegestaan	3000 m
Schokweerstand volgens IEC 60068-2-27	11 ms Pulse 25g
Weerstand tegen trillingen volgens IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations

BV-certificaat	1SAA971000-0201
CB-certificaat	1SAA971000-2001
CQC-certificaat	CQC2019010304197131
Declaration of Conformity - CCC	2020980304001602
Conformiteitsverklaring - CE	1SAD101100-3201
Declaration of Conformity - UKCA	1SAD201100-3201
RINA-certificaat	1SAA971000-0801
UL-certificaat	E191658-19880826

Container Information

Pakketniveau 1 Units	doos 1 stuk
Pakketniveau 1 Breedte	46 mm
Pakketniveau 1 Hoogte	70 mm
Pakketniveau 1 Lengte	49 mm
Pakketniveau 1 Brutogewicht	0.255 kg
Pakketniveau 1 EAN	4013614548765

Pakketniveau 2 Units	doos 10 stuk
Pakketniveau 2 Breedte	243 mm
Pakketniveau 2 Hoogte	80 mm
Pakketniveau 2 Lengte	106 mm
Pakketniveau 2 Brutogewicht	2.61 kg
Pakketniveau 2 EAN	4013614548963

Classifications

Object classificatiecode	Q
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Magneetschakelaar
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Magneetschakelaar
eClass	V11.0 : 27371003
UNSPSC	39121529
E-Number (Finland)	3709552

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Magneetschakelaars → Minischakelaars

