

## PCE data sheet

article#	<b>9216211</b>
article description	<b>CEE-motor protection plug contactor 12,5kW PI+BA+RFC 32A 5p 6h (16-20A) IP44</b>
description long	CEE-motor protection plug contactor 15kW PI+BA+RFC 32A 5p 6h (16-20A) IP44 housing material: Gummi rated current: 32A number of poles: 5 (3P+N+PE) clock-position: 6h rated voltage/frequency: 200/346V~ - 240/415V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals rotary switch (I-0-II), motor setting range: 16A - 20A, contactor: 12,5kW with phase inverter, operating display and rotation field check 2x cable gland M16, 1x M32 IP protection class: IP54
GTIN (EAN)	9003399666988
country of origin	AT
customs number	85366990
net weight	4.700 kg
packaging quantity	1

ETIM 7.0	EC000452
Type of motor protection	Thermal release
Type of control element	Rotary toggle
Phase inverter	True
Phase sequence monitoring	True
Adjustable current range	16 - 20 A
Colour plug	Red
Colour housing	Other
Rated voltage	400 V
Rated permanent current lu	32 A



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)