

# SLI035077NW\_PW

SLI035077NW\_PW



Power	<b>45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4950 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP44</b>

## Technical data


---

Code	SLI035077NW_PW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.95
Useful luminous flux*	4950 lm (360°)
Luminous flux**	4000 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>90
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	595x595x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity

