

LIMEA SLIM 2

SLI047005WW



See
more

Hermetic luminaire LIMEA SLIM 2, with a power of 60 W, high light efficacy 140 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with a warm light (3000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.




Power	60 W	Voltage	230 V
Luminous flux*	9600 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
IK	08	Degree of protection (IP)	IP66

Technical data

Code	SLI047005WW
Power	60 W
Nominal current	270 mA
Voltage	230 V
Energy consumption	60 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	9600 lm (120°)
Luminous flux**	8400 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-30/+40 °
Lifespan	50000 h
Housing material	plastic
IK	08
Degree of protection (IP)	IP66
Colour	White
Dimension (AxBxC)	1700x65x67 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	L80B10 50000h MTBF 80000h

Related documents



 Declaration of Conformity



 Photometric file

