

PRODUCT DATASHEET Decor Plaster Nest Table 1XG9 White

Decor Plaster | Decorative luminaires made of plaster with exchangeable light source



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- High-quality look and feel
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting
- Real wood used by some types

Product features

- Housing material: metal and plaster
- Textile cable




TECHNICAL DATA

Electrical data

| Nominal voltage | 220240 V |
|------------------|---------------|
| Mains frequency | 5060 Hz |
| Protection class | П |
| Operating mode | Mains voltage |

Dimensions & Weight

| Length | 325.00 mm |
|----------------|-----------|
| Width | 240.00 mm |
| Height | 135.00 mm |
| Product weight | 1350.00 g |
| Cable length | 1800 mm |



DECOR PLASTER NEST TABLE 1XG9 WT

Materials & Colors

| Product color | White |
|----------------|---------|
| Housing color | White |
| Body material | Plaster |
| Cover material | Glass |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|------------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Plug type C (EU) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |

| Dimmable | No |
|-------------------------|----------|
| Mounting type | Standing |
| Application environment | Indoor |
| Adjustable | No |
| With light source | No |
| Holder designation | G9 |

Certificates & Standards

| Standards | CE |
|-----------|----|

Additional product data

| Product remark | Maximum bulb wattage: 5 W LED |
|-----------------------|-------------------------------|
| Number of illuminants | 1 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|---|--|
| POF | User instruction / safety instructions | DECOR CLAY/CONCRETE/PLASTER NEST TABLE G9 | |
| PDF | Declarations of conformity | DECOR LUM | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075841444 | Folding box 1 | 144 mm x 302 mm x 503 mm | 1723.00 g | 21.87 dm ³ |
| 4058075841451 | Shipping box 2 | 520 mm x 318 mm x 313 mm | 4265.00 g | 51.76 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.