



MASTER UltraEfficient LED bulb

MAS LEDBulbND5.2-75W E27 840A70 CLG UE

This is the most efficient LED bulb from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

Product data

| General Information | |
|--|--------------------|
| Cap-Base | E27 |
| Nominal lifetime | 50,000 hour(s) |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| Flux measurement reference | Sphere |
| | |
| Light Technical | |
| Color Code | 840 [CCT of 4000K] |
| Luminous Flux | 1,095 lm |
| Color Designation | Cool White (CW) |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 210 lm/W |
| Color Consistency | <6 |
| Color rendering index (CRI) | 80 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Photobiological safety according to EN 62471 | RG1 |
| | |

| Operating and Electrical | |
|---------------------------|-------------|
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 5.2 W |
| Lamp Current (Nom) | 60 mA |
| Wattage Equivalent | 75 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.4 |
| Voltage (Nom) | 220-240 V |
| | |
| Temperature | |
| T-Case Maximum (Nom) | 70 °C |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |

A ↑ G


Α

MASTER UltraEfficient LED bulb

| Mechanical and Housing | |
|--|----------|
| Bulb Finish | Clear |
| Bulb Shape | A70 |
| Net Weight (Piece) | 0.050 kg |
| | |
| Approval and Application | |
| Energy Efficiency Class | A |
| Energy Consumption kWh/1000 h | 6 kWh |
| EPREL Registration Number | 1370040 |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| EyeComfort | Yes |
| Flickering value (PstLM) - Flickering value as | 1 |
| per EN 61000-3-3 | |
| Stroboscopic effect visibility measure (SVM) | 0.4 |
| | |
| Application Conditions | |
| can it be used in closed luminaires | No |


| Product Data | | |
|---------------------------------|---------------------------------|--|
| Order product name | MAS LEDBulbND5.2-75W E27 840A70 | |
| | CLG UE | |
| Full product name | MAS LEDBulbND5.2-75W E27 840A70 | |
| | CLG UE | |
| Full product code | 871951443589600 | |
| Order code | 929003480502 | |
| Material Nr. (12NC) | 929003480502 | |
| Numerator - Quantity Per Pack | 1 | |
| EAN/UPC - Product/Case | 8719514435896 | |
| Numerator - Packs per outer box | 10 | |
| EAN/UPC - Case | 8719514435902 | |
| | | |


Dimensional drawing



| Product | D | с |
|--|-------|--------|
| MAS LEDBulbND5.2-75W E27 840A70 CLG UE | 70 mm | 127 mm |
| | | |

Photometric data






Light Distribution Diagram - MAS LEDBulbND5.2-75W E27 840A70 CLG UE

General uniform lighting - MAS LEDBulbND5.2-75W E27 840A70 CLG UE


MASTER UltraEfficient LED bulb

Photometric data



Spectral Power Distribution Colour - MAS LEDBulbND5.2-75W E27 840A70 CLG UE

Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram - MAS LEDBulbND5.2-75W E27 840A70 CLG UE



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2025, March 17 - data subject to change