



product description: the bushings are designed to mechanically protect the conductors or cables coming from the steel pipe
plug the bushing from inside on the end of pipe before installing cables

material: PE

halogen-free: yes

color: gray

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

meets the requirements: EN 61386-1 ed.2:09, EN 61386-21:04

storage: ČSN 64 0090



chemical resistance: YES: acetone, ammonia 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
NO: aniline, chlorinated hydrocarbons, tetrachlorocarbon

item number	d1 (mm)	d2 outer Ø (mm)	weight 1pc (kg)	package (pcs)	for pipes
4913_XX	13,5	18,2	0,002	400 / 2800	6013..., 6213...
4916_XX	15,6	20,3	0,003	400 / 2000	6016..., 6216...
4921_XX	20,6	25,7	0,003	250 / 1250	6021..., 6221...
4929_XX	29,4	34,4	0,004	100 / 700	6029..., 6229...
4936_XX	38,4	44	0,006	80 / 400	6036..., 6236...
4942_XX	45,5	51	0,007	60 / 360	6042..., 6242...