



CorePro GLASS LED candles and lusters

CorePro LEDLusterND6.5-60W P45 E27840FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere

Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	806 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	55 °C

Controls and Dimming	
Dimmable	No

CorePro GLASS LED candles and lusters

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	P45 [P 45mm]

Approval and Application


Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	387,453
CE mark	Yes
EU RoHS compliant	Yes

Product Data

Full product code	871951434770000
-------------------	-----------------



Order product name	CorePro LEDLusterND6.5-60W P45 E27840FRG
Order code	929002029392
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929002029392
Full product name	CorePro LEDLusterND6.5-60W P45 E27840FRG
EAN/UPC - Case	8719514347717

Dimensional drawing



Product	D	C
CorePro LEDLusterND6.5-60W P45 E27840FRG	45 mm	78 mm


Photometric data



Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45 E27840FRG


CorePro GLASS LED candles and lusters

Photometric data




Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E27840FRG

Lifetime



Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45 E27840FRG



Life Expectancy Diagram - CorePro LEDLusterND6.5-60W P45 E27840FRG

