



Ledinaire SlimDownlight

DN065C G4 LED20/840 19W 220-240V 8-D225

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information	
Light source color	840 neutral white
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	110°
Connection	Screw connection block 2-pole
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	CE mark
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	55
EU RoHS compliant	Yes
Light source engine type	LED
Unified glare rating CEN	28
Lighting Technology	LED
Brand	Philips
Light Technical	
Luminous Flux	2,000 lumen

Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	80
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	19 W
Inrush current	4.92 A
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Metal-Plastic
Reflector material	-
Housing Color	White

Ledinaire SlimDownlight

Overall length	225 mm	
Overall width	225 mm	
Overall height	27 mm	
Overall diameter	225 mm	
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm	
Approval and Application		
Ingress protection code	IP20/40 [Finger-protected, Emitting	
	surface]	
Mech. impact protection code	IK03 [0.3 J]	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Init. Corr. Color Temperature	4000 K	
Power consumption tolerance	+/-10%	
Over Time Performance (IEC Compliant)		
Lumen maintenance at median useful life*	L65	


Product Data		
Full product code	871951446453700	
Order product name	DN065C G4 LED20/840 19W 220-240V 8-	
	D225	
Order code	929003251832	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material number (12NC)	929003251832	
Net weight	0.580 kg	
Full product name	DN065C G4 LED20/840 19W 220-240V 8-	
	D225	
EAN/UPC - Case	8719514464544	




Lumen maintenance at median useful life*

50000 h

Dimensional drawing



Photometric data



Light Distribution Diagram

Dawnight 4000K 19 1 x 9290022518		
		1 x 2000 in
Pelar Instaty dagram	Ounterminuter dagen UCK dag	~
128821	Aug 187	10 10 100
WORK!		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
NOV.		- Augustan
24		
	Unitaria fanor salis Gambaras	Tata
Manager 10		
COLUMN COURSE		
internet 10		

Philips Lighting B.Y.

Ledinaire SlimDownlight



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 12 - data subject to change