

# SLI042003CCT\_PW

SLI042003CCT\_PW

CCT

IP54

IK10



Power	<b>15 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1800 lm (360°)</b>	Colour temperature	<b>2700/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Degree of protection (IP)	<b>IP54</b>

## Technical data

---

Code	SLI042003CCT_PW
Power	15 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	15 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0,5
Useful luminous flux*	1800 lm (360°)
Luminous flux**	1650 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Plastic
IK	10
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	221x47 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC
Other	Light color change function 2700K/4000K/6000K ,

## Related documents

---



 User manual