| 29410199 | DATA SHEET |
|---------------------------|---|
| Valid from: 24.05.2018 | GOF Adapter Duplex SC Multimode BE /4PC |

Description

- GOF Optical fiber adapter SC-Duplex
- Singlemode- and multimode-type



General characteristics

Type of coupling SC-Duplex (SC-D) Flange Yes Attenuation < 0.2 dB

Temperature range -40 °C to +85 °C (-40 °F to 185 °F) (Operation)


Variation

| Article | Description | Housing colour | For fiber-type | Polishing |
|----------|--|----------------|-----------------|-------------------------------|
| 29410199 | GOF Adapter Duplex SC Multimode BE /4PC | Beige | Multimode (MM) | PC (physical contact) |
| 29410989 | GOF Adapter Duplex SC SM APC GR /4PC | Green | Singlemode (SM) | APC (angled physical contact) |
| 29410999 | GOF Adapter Duplex SC SM | Blue | Singlemode (SM) | PC (physical contact) |


Mechanical properties


V-0 Flame retardant acc. to UL 94 ABS Housing, material Guide sleeve, material Zirconia 1000 Mating cycles (min.)

Technical drawing



Coupling





Standard

Fibre optic connector interfaces - Part 4: Type SC

Application range

Office, Data centers, Industry

Photographs are not true to scale and do not represent detailed images of the respective products.

| Document: DB29410199EN | Dogo 1 of 1 |
|------------------------|-------------|
| Version: 00 | Page 1 of 1 |

IEC 61754-4