

PRODUCT DATASHEET

Decor Drums Pendant 3XGU10 2XLED Black

Decor Drums | Decorative luminaires made of aluminium with GU10 socket



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- High-quality look and feel
- High-quality housing with a matt black surface
- Minimalistic style fits to every room
- Different types of luminaires with the same design language maintain a consistent style at home
- Inline-switch for table and floor luminaire
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

Product features

- Housing material: aluminum
- Textile cable



TECHNICAL DATA

Electrical data


| | |
|---|---------------|
| Nominal wattage | 7.50 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 60.000 mA |
| Inrush current | 0.06 A |
| Inrush current time T_{h50} | 70 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 110 |
| Max. number of luminaires per miniature circuit breaker C10 | 88 |
| Max. number of luminaires per miniature circuit breaker C16 | 141 |
| Power factor λ | > 0.5 |
| Total harmonic distortion | 64 % |
| Protection class | II |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|--------------------|
| Luminous flux | 460 lm |
| Total luminous flux of contained light sources | 680 lm |
| Luminous efficacy | 61 lm/W |
| Color temperature | 3000 K |
| Reference control setting of contained light source (Kelvin) | 3000 K |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | 6 sdc _m |
| Flickering metric (Pst LM) | < 1 |
| Stroboscope effect metric (SVM) | < 0.4 |
| Photobiological safety group acc. to EN62778 | RG0 |
| Beam angle | 26 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 825.00 mm |
| Width | 56.00 mm |
| Height | 1240.00 mm |
| Product weight | 1685.00 g |



DECOR DRUMS PENDANT
3XGU10 2XLED BK

Materials & Colors

| | |
|--|--------|
| Product color | Black |
| Housing color | Black |
| Body material | Steel |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|------------------------------|-------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Suspended |
| With light source | No |
| Holder designation | GU10 |

Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |





Additional product data

| | |
|-----------------------|-------------------------------|
| Product remark | Maximum bulb wattage: 5 W LED |
| Number of illuminants | 2 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|--------------------|
|  | User instruction / safety instructions | |
|  | Legal information | DECOR DRUMS/CIRCLE |
|  | Declarations of conformity | DECOR LUM |
|  | Declarations of conformity UKCA | DECOR LUM |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075838581 | Folding box 1 | 112 mm x 137 mm x 873 mm | 1980.00 g | 13.40 dm ³ |
| 4058075838598 | Shipping box 4 | 890 mm x 245 mm x 300 mm | 8881.00 g | 65.42 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.