

PRODUCT DATASHEET SPC.T FR 10 W 225 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Baking ovens
- Domestic baking ovens




TECHNICAL DATA

Electrical data

| Nominal wattage | 10 W |
|----------------------|---------|
| Construction wattage | 10.00 W |
| Nominal voltage | 230 V |

Photometrical data

| Luminous flux | 30 lm |
|---|--------|
| Luminous efficacy | 3 lm/W |
| Lumen main.fact.at end of nom.life time | 0.80 |
| Color temperature | 2700 K |
| Color rendering index Ra | 100 |
| Light color | 1027 |



Light technical data

| Start | ing time | 0 s |
|-------|----------|-----|
| | | |

Dimensions & Weight

| Overall length | 57.00 mm |
|----------------|----------|
| Diameter | 25,0 mm |
| Product weight | 9.6 g |

Additional product data

| Base (standard designation) | | E14 | |
|-----------------------------|------------------|---------|--|
| | Mercury-free | Yes | |
| | Design / version | Frosted | |

Capabilities

| Dimmable | Yes |
|---|---------------------|
| Certificates & Standards | |
| Energy efficiency class | G |
| Energy consumption | 10.00 kWh/1000h |
| Country-specific categorizations | |
| ILCOS | IBT/F-10-230-E14-25 |
| Order reference | SPC.T25/57 FR 1 |
| Energy labelling regulation data acc EU 2019/2015 | |
| Lighting technology used | OTHER |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E14 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0 W |
| Networked standby power for CLS | 0 W |
| Claim of equivalent power | No |
| Length | 56.00 mm |
| Height | 25,0 mm |
| Width | 25,0 mm |
| Chromaticity coordinate x | 0.503 |
| Chromaticity coordinate y | 0.416 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 714466 |
| Model number | AC35395 |

DOWNLOAD DATA

Photometric and lighting design files



Spectral power distribution

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300102641 | Blister 2 | 122 mm x 20 mm x 85 mm | 37.00 g | 0.21 dm ³ |
| 4050300102658 | Shipping box 20 | 283 mm x 146 mm x 152 mm | 444.71 g | 6.28 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.