

# PRODUCT DATASHEET

## LS VAL -600/865/50

LED STRIP VALUE-600 50 meter reel | LED strips 50m long with 600 lm/m for general applications



### Areas of application

- General indoor illumination
- Cove lighting
- Bars, restaurants, hotels
- Residential interiors

### Product benefits

- Long LED strips for customized solutions made to measure
- Great design freedom thanks to flexibility and cuttability of module
- Maximum flexibility due to large range of accessories
- Easy installation, no tools required for connection

### Product features

- Flexible and cuttable LED strip
- Luminous flux: 600 lm/m
- Color rendering index  $R_a$ : > 80
- Lifetime (L70/B50): up to 20,000 h at  $T_c$  max.: 75°C
- Smallest cuttable unit: 100 mm
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)



## TECHNICAL DATA

### Electrical data

Nominal wattage	27.50 W
Construction wattage	27.50 W
Nominal wattage per meter	6.1 W <sup>1)</sup>
Nominal voltage	24 V
Input voltage range	23...25 V
Reverse Voltage	30 V
Type of current	DC
Nominal current	230 mA

<sup>1)</sup> Value based on first meter of the product

### Photometrical data

Luminous efficacy	100 lm/W <sup>1)</sup>
Luminous flux	2880 lm
Luminous flux per meter	610 lm <sup>1)</sup>
Color temperature	6500 K
Color rendering index Ra	> 80
Light color LED	Daylight
Light color (designation)	Cool Daylight
Standard deviation of color matching	≤5 sdc <sub>m</sub>

<sup>1)</sup> Value based on first meter of the product

### Light technical data

Beam angle	120 °
------------	-------

### LED MODULE INFORMATION

Number of LEDs per meter	60
Number of LEDs per smallest unit	6

### Dimensions & Weight



Length	50000.00 mm
Length – smallest unit	100 mm
Cable length	500.000
Width	8.00 mm
Height	1.50 mm
Prewired	Yes
Conductor cross section	0.5 mm <sup>2</sup>
LED pitch	16.67 mm
Short pitch	No
Product weight	1350.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	75 °C
Temperature range in operation	-20...+40 °C

### Lifespan

Nominal lamp life time	20000 h
------------------------	---------

### Capabilities

Dimmable	Yes <sup>1)</sup>
Lowest bending radius	15,0 mm
Self-adhesive	Yes

<sup>1)</sup> Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

### Certificates & Standards










Approval marks – approval	CE
Protection class	III
Type of protection	IP00
Energy consumption	3.10 kWh/1000h <sup>1)</sup>
Energy class of contained light source	F
Salt mist resistance acc. IEC 60068-2-52	No
UV resistance acc. IEC 60068-2-5	No












<sup>1)</sup> Value based on 0.5 meter












## LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

## Accessories Optional

Product image	Product name	EAN
	LS AY -PF01/UW/22X6/10/1	4058075278196
	LS AY -8/SMB	405807527588
	LS AY -CSW/P2/50	405807527434
	LS AY -CSD/P2	405807527526
	LS AY -CP/P2/500	405807527403
	LS AY -PF02/U/16X5/10/1	4058075278226
	LS AY -PM04/UW/23X15,5/10/1	4058075278400
	LS AY -PM02/R/18X15,5/10/1	4058075278349
	LS AY -PM01/UW/21,5X12/10/1	4058075278318

Product image	Product name	EAN
	LS AY -PM06/E/18X18/12/1	4058075279308
	LS AY -PM05/U/17,5X14,5/10/1	4058075279278
	DR DIM-PFM -60/220-240/24/P	4058075240018
	LS AY -PF01/UW/22X6/10/2	4058075401532
	LS AY -PF02/U/16X5/10/2	4058075401563
	LS AY -PF04/U/17X7/12/1	4058075278288
	LS AY -PM03/E/19X19/10/1	4058075278370
	LS AY -PW01/U/26X8/14/2	4058075401440
	LS AY -PW03/U/26X26/14/2	4058075401501
	LS AY -PW01/U/26X8/14/1	4058075278103
	LS AY -PF03/UW/25X7/12/1	4058075278257



Product image	Product name	EAN
	LS AY -PW02/UW/39X26/14/1	4058075278134
	DR DIM-PFM -40/220-240/24/P	4058075239999
	LS AY -PW02/UW/39X26/14/2	4058075401471
	LS AY -PW03/U/26X26/14/1	4058075278165
	DR-PFM -250/220-240/24/P	4058075240032
	DR-VAL -30/220-240/24	4058075240056
	DR-PFM -100/220-240/24/P	4058075239937
	DR-PFM -150/220-240/24/P	4058075239975
	DR-PFM -60/220-240/24/P	4058075239913
	DR-PFM -30/220-240/24/P	4058075239890
	DR DIM-PFM -250/220-240/24/P	4058075240155


Product image	Product name	EAN
	DR DIM-PFM -40/220-240/24/P	4058075379176
	DR-VAL -60/220-240/24	4058075240094
	DR DIM-PFM -150/220-240/24/P	4058075240117
	DR DIM-PFM -100/220-240/24/P	4058075240070
	DR-VAL -120/220-240/24	4058075240131
	DR-VAL -150/220-240/24	4058075240179
	DR DIM-PFM -60/220-240/24/P	4058075379190

**EQUIPMENT / ACCESSORIES**


– Connectors, profiles and covers for several mounting options available

**DOWNLOAD DATA**

Documents and certificates	Document name
 User instruction / safety instructions	LED STRIP VALUE IP00
 Legal information	LED STRIP VALUE 50m IP00

Documents and certificates		Document name
	Declarations of conformity	LS VAL Big Reel

---

Tender texts		Document name
	Tender documents	LED STRIP VALUE 600 50 meter reel 600 865 50-EN

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075597426	Folding box 1	242 mm x 242 mm x 26 mm	1893.00 g	1.52 dm <sup>3</sup>
4058075600812	Shipping box 10	516 mm x 496 mm x 332 mm	20346.00 g	84.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.