

PRODUCT-DETAILS

TSR Bell and buzzer



General Information	
Extended Product Type	TSR
Product ID	2CSM100000R0831
EAN	8012542369608
Catalog Description	TSR Bell and buzzer
Long Description	Bell characterized by discontinuous use through one or more pushbuttons, suitable for public and tertiary acoustic signalling.

Technical	
Standards	EN 62080
Rated Operational Voltage	230 V AC
Primary Voltage	230 V AC
Rated Frequency (f)	50 Hz
	5.5 V·A
Sound / Tone Type	Intermittent
Sound dB (A)	Bell (1 m) 80 dB Buzzer (1 m) 70 dB Threetones (1 m) 84 dB
Options Provided	Transformer included
Mounting Position	Vertical only
Remarks	Discontinous operations: the device need rest time between two consecutive functionings
Cable Cross-Section	Maximum 10 mm²

TSR 2

Environmental	
Degree of Protection	IP40
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	2CSC446002K0201
REACH Declaration	9AKK108467A9482
Environmental Information	See RoHS Information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	0.085 m
Product Net Depth / Length	0.075 m
Product Net Weight	0.300 kg
Ordering	
Minimum Order Quantity	1 piece
Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	1.654 kg
Certificates and Declarations	
Declaration of Conformity - CE	2CSC446002K0201
Installation	
Instructions and Manuals	9AKK107991A8334
instructions and wantans	SARCIO/33 PAGGG
Popular Downloads	
Data Sheet, Technical Information	9AKK107991A8334
Classifications	
ETIM 8	EC001547 - Bell transformer
ETIM 9	EC001547 - Bell transformer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8 eClass	85043121 V11.0 : 27031190
Object Classification Code	V11.0.27031190 H
Object Glassification Gode	П

TSR 3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Command\ and\ Signalling\ Devices \rightarrow Bells\ and\ buzzers$

